

flowtech™ 100

Tripod



Part No. C1266-0001

Copyright © 2019

All rights reserved.

Original Instructions: English

All rights reserved throughout the world. No part of this publication may be stored in a retrieval system, transmitted, copied or reproduced in any way, including, but not limited to, photocopy, photograph, magnetic or other record without the prior agreement and permission in writing of Videndum Plc.

Disclaimer

The information contained in this publication is believed to be correct at the time of printing. Videndum Production Solutions Ltd reserves the right to make changes to the information or specifications without obligation to notify any person of such revision or changes. Changes will be incorporated in new versions of the publication.

We are making every effort to ensure that our publications are updated on a regular basis to reflect changes to product specifications and features. Should this publication not contain information on the core functionality of your product, please let us know. You may be able to access the latest revision of this publication from our website.

Videndum Production Solutions Ltd reserves the right to make changes to product design and functionality without notification.

Trademarks

All product trademarks and registered trademarks are the property of Videndum Plc.

All other trademarks and registered trademarks are the property of their respective companies.

Published by:

Videndum Production Solutions Ltd

Supports Technical Publications Department

Email: technical.publications@Videndum.com



Video tutorials are available, if required please contact support@Videndum.com for further details.

Safety	2	Opening Tripod Legs	14
Warning symbols used in these instructions	2	Alternative Locking Method	16
Health and Safety	2	Close Tripod Legs	17
Mounting and Installation	2	Accessories	18
About this guide	3	Fit Supplied Attachment Mount	18
Intended use	3	Fit Optional Carry Strap	18
Warranty	3	Attach Optional Rubber Feet	19
Extended warranty	3	Fit Carry Handle (S2051-1057)	19
About This Guide	3	Maintenance	20
Operating Elements	4	Cleaning	20
Optional Accessories	5	Flush the Tripod	20
Installation	6	Hinge Lock Cleaning	20
Setting up the Tripod	6	Checking brake force	21
Attach Optional Mid-Level Spreader flowtech 100	7	Adjusting brake force	22
Operation of Mid-Level Spreader flowtech 100	7	Leg Friction Adjustment	23
Cleaning	8	Specification	24
Attach Optional Ground Spreader flowtech 100	9	100 mm Tripod	24
Operation of Ground Spreader	10		
Closing Tripod with Ground Spreader Attached	11		
Remove Foot from Spreader	12		
Cleaning	12		
Using Locks When no Spreader Used	13		
No Spreader Mode	13		
Spreader Mode	13		

Safety

Important information on the safe installation and operation of the product. Read this information before operating the product. For your personal safety, read these instructions. Do not operate the product if you do not understand how to use it safely. Save these instructions for future reference.

Warning symbols used in these instructions

Safety cautions are used in these instructions. These safety instructions must be followed to avoid possible personal injury and possible damage to the product.



WARNING! Where there is a risk of personal injury or injury to others, comments appear supported by the warning triangle symbol. Where there is a risk of damage to the product, associated equipment, process or surroundings, comments appear supported by the word '**CAUTION**'.

Health and Safety



WARNING! Risk of personal injury or injury to others. All personnel must be fully trained and adhere to correct manual handling techniques and Health & Safety regulations. It is the responsibility of the local organisation to enforce safe working practices at all times.

Mounting and Installation



WARNING! Do not exceed the maximum payload capacity.



WARNING! Tripod spike feet can be dangerous, take care when handling. Always place tripod on the ground before releasing quick release levers.



WARNING! Risk of finger entrapment. Avoid trapping fingers when operating the tripod.



WARNING! Trip hazard. Set the tripod footprint to suit the shooting environment.



WARNING! Toppling hazard. Do not leave unattended. Keep out of reach of children.



WARNING! When in use always lock the tripod leg clamps to prevent the tripod collapsing.



WARNING! When releasing the quick release levers, be prepared to support the weight of any attached payload. **The levers are only sufficiently locked when in the fully closed (down) position.**



CAUTION! Always hold the payload securely when making adjustments to the tripod height or footprint.



CAUTION! Do not place your foot or heavy weight onto the spreader.



CAUTION! Always remove the camera before transporting.

About this guide

This user guide is an important part of the product and is aimed at the personnel who operate and maintain the tripod. It contains information about the tripod and its proper use and serves to safeguard users and their equipment.

Intended use

This tripod has been designed for professional use in television studios and outside locations for supporting fluid heads and cameras. Any use above and beyond this purpose is deemed improper and will void the warranty.

Warranty

The product is covered by a one year warranty.

The warranty will be invalidated if:


- The tripod is improperly installed or used in a manner contrary to this user guide.
- The tripod housing is opened by unauthorised personnel.

We reserve the right to make changes to the product based on technological advances.

Extended warranty

Please register at www.ocon.com for an extended warranty period.


Operating Elements



Pos No.	Description
1	Hinge Lock Slider
2	Hinge Lock Button
3	Double-spiked Foot
4	Leg Magnetic Clasp
5	Quick Release Lever
6	Accessory Dock x 3
7	Attachment Mount

Optional Accessories

Pos No.	Description	Part No.
1	Rubber Feet	V4150-1901
2	Mid-level Spreader flowtech 100	V4161-0001
3	Attachment mount	V4150-1900
4	Carry Strap kit	V4150-1851
5	Carry Handle c/w Hex Key	S2051-1061
6	Ground Spreader	V4162-0001



Installation

Setting up the Tripod

1. The legs are secured using magnetic catches. Pull the legs from the bottom to separate.

Note! If preferred this step may be performed after step 3.

2. Place the tripod on the ground. Lift the quick release levers fully and raise the tripod to the required height.

3. With the correct height achieved, lower the quick release levers to lock the legs in position.




WARNING! The legs are only sufficiently locked when the locking levers are in the fully closed (down) position.




WARNING! Tripod spiked feet can be dangerous. Always place tripod on the ground before releasing quick release levers.


1



2



3



Attach Optional Mid-Level Spreader flowtech 100




CAUTION! Ensure the latching pins are fully engaged with the locating holes in the tripod. Failure to attach correctly could result in damage to the equipment




The tripod is delivered with the Hinge Lock in the OFF position for use with a spreader. (See page 14 for lock operation).

1. Hold the spreader between thumb and forefinger and squeeze the release buttons on each side.




2. Align the latching pins with the locating holes on the tripod leg.
3. Release the buttons to lock the spreader in place.



Operation of Mid-Level Spreader flowtech 100

1. Press and hold the arm release button (as below).
2. Extend the inner arm to the required length and release the button.

Visual Distance Markers



NOTE! The inner arm should not be pushed back against the ratchet mechanism, always hold the release button down whilst extending or retracting the inner arm.

The inner section has three distance markers (as shown above), this helps to visually set the length of the spreader arms.








If the spreader will not go into the desired position, check the tripod Hinge Lock is in the OFF (spreader mode) position for use with a spreader. (See page 13 for lock operation).

Installation

The spreader has 4 x locking positions 50, 40, 30 and 0°

1. Rotate the adjustment cap on top of the spreader, anticlockwise to allow the spreader to open to the selected setting.
2. A positive click will be felt as each position is achieved.



Cleaning.

After each use, brush off any dirt or debris, if necessary wash down with clean water.

Attach Optional Ground Spreader flowtech 75 / 100




CAUTION! Ensure the ground spreader legs are all the same length before attempting to fold the tripod with the spreader attached. Failure to observe this procedure could lead to damage of the Ground Spreader




The tripod is delivered with the Hinge Lock in the OFF position for use with a spreader. (See page 14 for lock operation).


Ground Spreader shown in the stored position



1. Place the spreader flat on the floor.




2. Place the tripod foot on the ball of the spreader foot.




Installation

3. Bend the rubber strap **1** and engage the bottom edge of the lever in the tripod recess.
4. Lift the lever **2** upwards towards the tripod until it locks in place. Repeat for all three legs.



5. Tripod spiked foot secured in the Ground Spreader Foot.




Operation of Ground Spreader

1. When assembled on the tripod, use your foot to press and hold the arm release button (as below).
2. Extend the inner arm to the required length and release the button. (There are a total of 12 positions).



NOTE! The inner arm should not be forced back against the mechanism, always hold the release button down whilst extending or retracting the inner arm.

The inner section has distance markers (as shown below), this helps to visually set the length of the spreader arms.



If the spreader will not go into the desired position, check the tripod Hinge Lock is in the OFF (spreader mode) position for use with a spreader. (See page 13 for lock operation).

Closing Tripod with Ground Spreader Attached


1. To close the tripod legs, ensure all the spreader legs are set at the same distance.
2. Lift the spreader using the centre knob, then close the legs as normal.



CAUTION! Ensure the ground spreader legs are all the same length before attempting to fold the tripod with the spreader attached. Failure to observe this procedure could lead to damage of the Ground Spreader




The tripod can be closed with the spreader legs at minimum to maximum extension, as long as they are all set at the same length



Installation

Remove Foot from Spreader

1. To remove the feet from the spreader, push the foot release button towards the centre of the spreader.
2. Lift the foot from the spreader.
3. Reverse the procedure to re-attach the feet to the spreader



The spreader can be removed from the feet while they are still attached to the tripod

Cleaning.


After each use, brush off any dirt or debris, if necessary wash down with clean water.

Using Locks When no Spreader Used



The tripod can be used without a spreader using the three lock positions.

1. The tripod has 3 x lock positions 20°, 46° and 72°.



Caution! Risk of damage. Only use the 72° hinge lock setting with the legs in the fully retracted position. Do not apply excessive load.




Caution! Risk of damage. In **No Spreader Mode** (Hinge Lock **ON**) position, ensure that the feet are free to adapt to a new footprint area when raising or lowering the tripod.

No Spreader Mode

2. With the lock in the raised position the lock is **ON**.


Hinge Lock Slider in the engaged (**ON**) position.
(Leg will stop at pre-set positions)



Spreader Mode

3. With the lock in the lower position the lock is **OFF**.

Hinge Lock Slider in the neutral (**OFF**) position.
(Legs free to move through full movement)




Caution! Risk of damage. When using with a spreader or dolly, ensure the Hinge Lock Slider is in the **OFF** position.

Installation

Opening Tripod Legs


The first position at 20° is likely to be the most used position.

1. Press the lock button to engage the lock. (No Spreader Mode)
2. Pull the leg outward and it will stop at the 20° lock position.




The angle of each leg can be adjusted independently of the other two legs.


3. To select the 46° or 72° position, disengage the lock.
 - a. As a safeguard against accidental collapse the leg must be moved inwards slightly **1** to relieve the tension on the lock.
 - b. Push the lock slider down **2** and pull the leg outwards **3**.




3. Move the leg past the 20° position.
4. Engage the Lock Slider by pushing the Hinge Lock Button.



5. Continue pulling the leg until it stops at the 46° lock position.



6. Repeat procedure for the 72° position.




7. Repeat for the remaining legs as required.


Installation

Alternative Locking Method

1. An alternative method would be to release the Hinge Lock, and fully open the leg to 90°




2. Engage the lock.



WARNING! Risk of finger entrapment. Avoid trapping fingers when operating the tripod.

3. Move the leg towards the body. As the leg passes each lock point, an audible click will be heard, the leg is prevented from opening past this point again without disengaging the lock first.



Close Tripod Legs

1. The legs may be closed with or without the Lock being engaged.
2. Ensure the tripod legs are fully collapsed before moving them inward.




WARNING! Risk of finger entrapment. Avoid trapping fingers when closing the tripod.



The tripod is designed to accommodate the Mid-Level Spreader when collapsed.


3. Ensure the magnetic clasps have engaged and the legs are securely held.



Accessories


Fit Supplied Attachment Mount

1. There are three accessory docks. These can be used to dock the supplied attachment mount, Variable Friction Arm etc..
2. Offer the accessory to the docking point on the tripod head.
3. Insert the screw and tighten clockwise using a 5mm Hex key, tighten firmly.
4. Follow the same procedure to attach optional accessories to the remaining mounting points if required.




Fit Optional Carry Strap

1. Fit the attachment mount as previous section: "**Fit Supplied Attachment Mount**".
2. Fit the split ring to the mounting point at the bottom of the upper section.
3. Attach the strap clasps to the mounting points.




Attach Optional Rubber Feet

1. Place the rubber foot between the spikes. Check the marking on the foot for the correct orientation. The 'flowtech' marking must face outwards.




2. Bend the rubber strap **1** and engage the bottom edge of the lever in the tripod recess.
3. Lift the lever **2** upwards towards the tripod until it locks in place.




Fit Carry Handle (S2051-1057)

To attach the handle to one of the accessory docks.

1. Using a small screwdriver, lever the plug from the top of the handle to reveal the mounting screw.



2. Using the supplied Hex key, align the mounting screw in the handle with the accessory dock and tighten clockwise, as shown below. Ensure the handle is secure. Insert the plug back into the handle, ensuring the groove is uppermost and it is firmly pushed home.



Cleaning



Video tutorials are available, if required please contact support@Videndum.com for further details.



CAUTION! Do not use solvent or oil based cleaners, abrasives or wire brushes to remove accumulations of dirt as these will damage the protective surfaces. Use clean water only.

During normal use the only cleaning required is a periodic wipe-down with a lint-free cloth. Any dirt that accumulates during storage or periods of non-use may be removed with a vacuum cleaner. Particular attention should be paid to the ball base of the tripod.

Use out-of-doors under adverse conditions will require special attention. Salt spray should be washed off with fresh water at the earliest opportunity. Sand and dirt acts as an abrasive and should be removed using a semi-stiff brush or vacuum cleaner.

If exposed to extreme conditions, sand or grit could enter the tripod. This will require flushing to remove any contaminants.

Flush the Tripod

1. Place the tripod in a bucket of clean, 30 cm deep water.
2. Release the quick release levers and extend tripod fully.
3. Keeping the feet in the water, collapse and extend the tripod repeatedly, forcing water through the leg sections until the leg moves freely with no sign of sticking or contamination.
4. If required turn the tripod upside down and repeat.
5. Wipe down the outer surface with a clean dry cloth.


Hinge Lock Cleaning

The Hinge lock is designed so that sand or other debris may be worked out of the hinge lock mechanism.

Repeatedly operate the button and hinge slider, combined with blowing out the debris until the mechanism operates smoothly.


Should this procedure fail to sufficiently clear the debris, follow the instructions below to disassemble the mechanism for cleaning.

1. Pull the leg out to gain access to the M4 lock screw.
2. Using a 2.5mm or $\frac{3}{32}$ " ball ended hex key, remove the M4 lock screw by turning anticlockwise.




Caution! If the screw is dropped in the lock mechanism, do not try to close the leg. Turn the tripod upside down and shake the screw out or retrieve using pliers.

3. With the screw removed raise the leg to the horizontal position and push the hinge slider towards the bowl and lift out.



4. Lift out the hinge lock button.




5. Use compressed air and a soft brush to remove any debris.



WARNING! When using compressed air, wear suitable safety glasses to avoid injury.

6. Work the hinge lock up and down using the flat edge of a screw driver pushing on the centre of the lock, debris will work its way out the bottom of the mechanism.



7. Once the lock is clean assembly is a reversal of steps 2 - 4.



Caution! When replacing the M4 lock screw, offer it to the thread and turn anticlockwise until you hear / feel a click then tighten clockwise. This will prevent the screw from being cross threaded.

Checking brake force

Periodically check the effectiveness of the leg brake force and adjust if necessary.

1. Extend the middle and lower sections to 20 cm each.
2. Place a rubber mat or similar on a set of scales to prevent damage and skidding. Stand one leg on a set of scales and apply a vertical downward force.




WARNING! Use a non-slip mat to ensure the foot does not slip from the scales when applying downward pressure.

WARNING! Finger entrapment. Take care not to trap fingers.

flowtech 100	
✗	< 30 kg (66 lb)
✓	30 - 40 kg (66 - 88 lb)
✗	> 40 kg (66 lb)

3. With an average downward force of 30 - 40 kg (66 - 88 lb) applied, the leg should remain extended.
4. If the leg starts to collapse before a 30 kg (66 lb) force is achieved then adjustment is required.
"See Adjusting brake force".




Average slip force

Adjusting brake force

1. Lift the quick release lever to clear the adjustment screw. Using a 2.5mm or $\frac{3}{32}$ " hex key, turn clockwise to increase the brake force.
2. 10 full turns = 2 kg (4.4 lb) of additional brake force.



CAUTION! Do not adjust more than required as this will lead to increased wear and stress on the brake components.




3. When the adjustment is made, test the brake force again on the scales, repeat if necessary.
4. Repeat the procedure for the remaining two legs.




Should the adjustment range become insufficient to achieve the correct brake force, please contact your local service centre.
www.ocon.com

Leg Friction Adjustment

1. Should the leg friction require adjustment, open the legs to gain access to the M5 friction screws on the underside of the tripod.
2. The correct torque for these M5 screws is 2.5Nm to 3.5Nm Max.



3. Use a torque screwdriver to adjust the M5 screws to the correct torque. (2.5Nm to 3.5Nm Max)
4. Always tighten the screws in an opposite pattern following the numbered pattern in the diagram.
5. If a torque screwdriver is not available, use a Hex Key; follow the pattern in the diagram, but only tighten the screws by a small amount taking care not to over-tighten.
6. Test the legs for correct friction and adjust again if necessary.



CAUTION! Do not adjust more than required as this will lead to increased wear and stress on the leg friction components and damage to the bowl.

Specification

	100 mm Tripod		100 mm Tripod
 Bowl	100mm	 Maximum Operational Height On Mid-Level Spreader	155 cm (61.00 in.)
 Maximum payload	30 kg (66 lb)	 Minimum Operational Height On Mid-Level Spreader	52 cm (20.47 in.)
 Weight Tripod Only	3.2 kg (7.01 lbs)	 Maximum Operational Height On Ground Spreader	159 cm (62.5 in)
 Transport Length	68 cm (26.7 in.) Excluding rubber foot.	 Minimum Operational Height On Ground Spreader	43 cm (16.9 in)
 Operational Temperature	-40°C to 60°C (-40°F to 140°F)	 When used without rubber feet the tripod height will decrease by up to 1.8 cm.	
 Maximum Operational Height (On Hinge Lock)	153 cm (60.23 in.)	 Material	Carbon Fibre
 Minimum Operational Height (On Hinge Lock)	26 cm (10.23 in.)	 Extensions	X2

Technical specifications are subject to change without notice.

Publication No. C1266-4980 /1

oconnor



OConnor
A Videndum plc Brand

www.Ocon.com